

Product Specifications

Style Number	VV023	
Construction	Waterproof Foamed Core	
Edge Profile	Micro Bevel	
Nominal Dimensions	5" wide, 48" long	
	US Units	Metric Units
Actual Product Width	4.96"	13 cm
Actual Product Length	48.03"	122 cm
Wear Layer Thickness	20 mil (0.02")	0.5 mm
Overall Product Thickness	0.314"	8 mm
Core Thickness	0.256"	6.5 mm
Attached Underlayment	Attached Cork	
Attached Underlayment Thickness	0.059"	1.5 mm
Finish	UV Acrylic	
Installation Methods	Floating or Direct Glue	
Profile	Angle/Tap	
Country of Origin	Imported	

Packaging

Area per Box	26.47 sq ft	2 sq m
Pieces per Box	16 pcs	
Weight per Box	44.09 lbs	19.99 kg
Boxes per Pallet	42 boxes	



201 Gold Coast Acacia

Colors



COREtec Originals Classics VV023



The list of colors below complements the entire range of colors available for the current product.

1 Test

Performance

Static Load (ASTM F970)	Passes
Residual Indentation (ASTM F1914)	Passes
Resistance to Heat (ASTM F1514)	Passes
Resistance to Light (ASTM F1515)	Passes
Resistance to Chemicals (ASTM F925)	Passes
Radiant Panel (ASTM E648)	Passes, Class I
Slip Resistance (ASTM D2047)	ADA compliant

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Warranties

USF Lifetime Limited

[Residential Resilient Limited Warranty - Defects, Wear, Waterproof, Petproof](#)

USF 10 Year Light Commercial

Com Ub Bond 4100/4151

COREtec Originals Classics VV023

Certifications

FloorScore Certified


GreenGuard (Certification, Gold, Private Label) Certified

Coordinating Trim




Baby Threshold*

BT7CT | 94"
01V02 | 94"
01V04 | 94"




T-Molding*

TM7CT | 94"
02V24 | 94"
02V26 | 94"




Quarter Round

QTRCT | 94"
01V27 | 94"
01V29 | 94"




Overlap Stairnose*

01V76 | 94"
01V78 | 94"



Flush Stairnose

FS7HU | 94"
02V01 | 94"
02V04 | 94"



Overlap Reducer

01V52 | 94"
01V54 | 94"

*Packaged with molding track

Coordinating Metal Trim



Reducer

USC20
USC21
USC22



T-Mold

USC23
USC24
USC25



Stair Cap

USC17
USC18
USC19

Finish
Satin Silver
Satin Nickel
Dark Bronze

Installation Range

Profile Size	Installation Range
3.5mm	1.5mm to 3.5mm heights
5.5mm	3.6mm to 5.5mm heights
8mm	6mm to 8mm heights

Stair Tread



Stair Tread

03Z70 | 48"

