

Product Specifications

Style Number	VV012
Construction	Waterproof Foamed Core
Edge Profile	Enhanced Painted Bevel
Nominal Dimensions	7" wide, 48" long

	US Units	Metric Units
Actual Product Width	7.09"	18 cm
Actual Product Length	48.03"	122 cm
Wear Layer Thickness	20 mil (0.02")	0.5 mm
Overall Product Thickness	0.314"	8 mm
Core Thickness	0.256"	6.5 mm
Attached Underlayment	Attached Cork	
Attached Underlayment Thickness	0.059"	1.5 mm
Finish	UV Acrylic	
Installation Methods	Floating or Direct Glue	
Profile	Angle/Tap	
Country of Origin	Imported	

Packaging

Area per Box	23.64 sq ft	2 sq m
Pieces per Box	10 pcs	
Weight per Box	39.68 lbs	17.99 kg
Boxes per Pallet	35 boxes	




753 Axial Oak

Colors



COREtec Originals Enhanced VV012



Performance

Resistance to Heat (ASTM F1514)	Passes
Resistance to Light (ASTM F1515)	Passes
Radiant Panel (ASTM E648)	Passes, Class I
Slip Resistance (ASTM D2047)	ADA compliant

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Warranties

USF Lifetime

[Residential Resilient Limited Warranty - Defects, Wear, Waterproof, Petproof](#)

USF 10 Year Medium Commercial

Certifications

GreenGuard (Certification, Gold, Private Label) Certified


Coordinating Trim



Baby Threshold*


01V19 | 94"

01V20 | 94"




T-Molding*

02V62 | 94"




Quarter Round

01V46 | 94"



Overlap Stairnose*

01V95 | 94"



Flush Stairnose

02V17 | 94"

*Packaged with molding track

Stair Tread



Stair Tread

03Z70 | 48"

